



Eradicate 55

High Performance Floor Stripper



Eradicate 55 High Performance Floor Stripper is our fastest acting formula with powerful active ingredients, allowing it to rapidly remove heavy floor finish build-up. It begins to emulsify floor finish immediately upon contact. Eradicate 55 makes stripping a floor easier and faster. Conventional floor strippers cannot produce acceptable results after lengthy periods between stripping operations. Eradicate 55 addresses these concerns and produces excellent results even after numerous scrub and re-coats.

SURFACES



VCT TERRAZZO MARBLE QUARRY TILE

DO NOT USE ON ASPHALT, ASBESTOS TILE, WOOD, RUBBER, OR PAINTED SURFACES

DIRECTIONS

- Mix stripper with cold water per the following dilutions:
Heavy coating removal: 1:4 (32 oz per gallon/ 250 ml per 1 liter of water)
Normal coating removal: 1:6 (21.5 oz per gallon/ 166 ml per 1 liter of water)
Light coating removal: 1:8 (16 oz per gallon/ 125 ml per 1 liter of water)
- Apply solution liberally to the floor and allow to soak for 10 minutes ensuring the solution does not dry.
- Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
- Rinse thoroughly with clean water and allow floor to dry completely before applying any finish.

NOTE: Test floor for color fastness in an inconspicuous area

TECHNICAL DATA

Description	Fast acting floor stripper
Appearance	Clear blue liquid
Flash Point <small>ASTM D56-05 (2010)</small>	150°F (66°C)
Viscosity <small>@ 68°F (20°C)</small>	<10 centipoise
VOC <small>40 CFR Part 59 Subpart C</small>	54.5% (as supplied) 5.8% (1:8) 10.5% (1:4)
Fragrance	Floral fragrance
Shelf Life <small>ASTM D1791-93 (2008)</small>	2 years
Density <small>ASTM D1475-98 (2008)</small>	8.0 lb/gal @ 68°F 0.96 kg/L @ 20°C

PRODUCT INFO

Product Code	15525
Volume	2.5 US gallon
Shipping Package	2 x 2.5 gallons
Pallet Quantity	48



Hummelstown, PA 17036

(877) 843-3070

www.ameritechproducts.net