



# Gem Gloss

## High Gloss Floor Finish



A metal cross-linked, all-purpose, ultra high speed (“UHS”) coating, Gem Gloss High Gloss Floor Finish produces a tough, long lasting base and a diamond-like brilliant wet-look shine in an ultra high speed burnishing program.

### SURFACES



VCT    TERRAZZO    CONCRETE    MARBLE    QUARRY TILE

### DIRECTIONS

1. For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 5-6 thin coats using a clean synthetic mop. Allow the floor to dry thoroughly between coats and prior to burnishing.
2. Optional: Apply 2 thin coats of floor sealer for old or porous floors or for high traffic areas, then apply 4 coats of finish
3. For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

### PRODUCT INFO

**Product Code** 10525  
**Volume** 2.5 US gallon  
**Shipping Package** 2 x 2.5 gallons  
**Pallet Quantity** 48

### TECHNICAL DATA

<b>Coverage</b>	<b>2500-3000 Sq Ft/GL</b>
<b>Buffability</b>	<b>Excellent</b>
<b>Appearance</b>	<b>Milky White</b>
<b>Fragrance</b>	<b>Slight ammoniacal</b>
<b>Removability</b> <small>ASTM D1792-06</small>	<b>Excellent</b>
<b>Non-Volatile Solids</b> <small>ASTM D2834-95 (2008)</small>	<b>18%</b>
<b>Slip Resistance</b> <small>ULTM410</small>	<b>Meets Requirements</b>
<b>Detergent Resistance</b> <small>ASTM D3207-92 (2008)</small>	<b>Excellent</b>
<b>Specular Gloss (60°F)</b> <small>ASTM D1455-87 (2008)</small>	<b>&gt; 85</b>
<b>Shelf Life</b> <small>ASTM D1791-93 (2008)</small>	<b>1 Year</b>
<b>Drying Time</b>	<b>About 30 minutes</b>
<b>Viscosity</b> <small>@ 68°F (20°C)</small>	<b>&lt; 10 centipoise</b>
<b>Density</b> <small>ASTM D1475-98 (2008)</small>	<b>8.5 lb/GL @ 68°F</b>
<b>VOC</b> <small>40 CFR Part 59 Subpart C</small>	<b>0.07%</b>
<b>Freeze/Thaw</b> <small>ASTM D3209-93 (2008)</small>	<b>Passes 3 cycles</b>
<b>Density</b> <small>ASTM D1475-98 (2008)</small>	<b>8.6 lb/gal @68°F 1.03 kg/l @ 20°C</b>



**Hummelstown, PA 17036**  
**(877) 843-3070**  
[www.ameritechproducts.net](http://www.ameritechproducts.net)