Luminescent

Ultra High Speed Floor Finish

Luminescent is a high performance, ultra-high speed (UHS) and high gloss floor finish. Designed with the latest polymer and floor finish technology, Luminescent Floor Finish produces a spectacular off-the-mop shine. This 25% high solids finish is ideal for high traffic and high maintenance facilities such as schools and retail stores, but it also holds its shine incredibly well in low maintenance applications.

SURFACES

| VCT | TERRAZZO | CONCRETE | MARBLE | QUARRY TILE |

DIRECTIONS

1. For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 4-5 thin coats using a clean synthetic mop. Allow the floor to dry thoroughly between coats and prior to burnishing.
2. Optional: Apply 2 thin coats of floor sealer for old or porous floors or for high traffic areas, then apply 2-3 coats of finish.
3. For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

PRODUCT INFO

Product Code	10425
Volume	2.5 US gallon
Shipping Package	2 x 2.5 gallons
Pallet Quantity	48

TECHNICAL DATA

Coverage	2500 to 3000 ft²/gal 61 to 74 m²/liter
Buffability	Excellent
Appearance	Milky white
Fragrance	Mild odor, no fragrance added
Removability ASTM D1792-06	Excellent
Non-Volatile Solids ASTM D2834-95 (2008)	25%
Slip Resistance ULTM410	Meets requirements
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Specular Gloss (60°F) ASTM D1455-87 (2008)	>85
Shelf Life ASTM D1791-93 (2008)	1 year
Drying Time	About 25 minutes
Viscosity @ 68°F (20°C)	<10 cenitpoise
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.03 kg/L @ 20°C
VOC 40 CFR Part 59 Subpart C	0.06%
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.03 kg/L @ 20°C