



# Endura Gloss 20

*High Gloss, Low Maintenance Floor Finish*



ENDURA GLOSS 20 is an excellent, low maintenance coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing.

## SURFACES



VCT    TERRAZZO    CONCRETE    MARBLE    QUARRY TILE

## DIRECTIONS

1. For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 5-6 thin coats using a clean synthetic mop. Allow the floor to dry thoroughly between coats and prior to burnishing.
2. Optional: Apply 2 thin coats of floor sealer for old or porous floors or for high traffic areas, then apply 4 coats of finish.
3. For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

## PRODUCT INFO

**Product Code** 10325

**Volume** 2.5 US gallon

**Shipping Package** 2 x 2.5 gallons

**Pallet Quantity** 48

## TECHNICAL DATA

<b>Description</b>	Polymer emulsion
<b>Appearance</b>	Milky white
<b>Specular Gloss (60°)</b> <small>ASTM D1455-87 (2008)</small>	>85
<b>Viscosity (Brookfield)</b> <small>@ 68°F (20°C)</small>	<10 centipoise
<b>Coverage Rate</b>	2500 to 3000 ft <sup>2</sup> 61 to 74 m <sup>2</sup> /liter
<b>Dry Time</b>	About 30 minutes
<b>Removability</b> <small>ASTM D1792-06</small>	Excellent
<b>VOC</b> <small>40 CFR Part 59 Subpart C</small>	0.01%
<b>Non-Volatile Solids</b> <small>ASTM D2834-95 (2008)</small>	20%
<b>Fragrance</b>	Slight ammoniacal
<b>Slip Resistance</b> <small>ULTM410</small>	Meets requirements
<b>Shelf Life</b> <small>ASTM D1791-93 (2008)</small>	1 year
<b>Density</b> <small>ASTM D1475-98 (2008)</small>	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C
<b>Detergent Resistance</b> <small>ASTM D3207-92 (2008)</small>	Excellent
<b>Freeze/Thaw</b> <small>ASTM D3209-93 (2008)</small>	Passes 3 cycles



Hummelstown, PA 17036

(877) 843-3070

[www.ameritechproducts.net](http://www.ameritechproducts.net)