



# Luminescent

## Ultra High Speed Floor Finish



Luminescent is a high performance, ultra-high speed (UHS) and high gloss floor finish. Designed with the latest polymer and floor finish technology, Luminescent Floor Finish produces a spectacular off-the-mop shine. This 25% high solids finish is ideal for high traffic and high maintenance facilities such as schools and retail stores, but it also holds its shine incredibly well in low maintenance applications.

### SURFACES



### DIRECTIONS

1. For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 4-5 thin coats using a clean synthetic mop. Allow the floor to dry thoroughly between coats and prior to burnishing.

NOTE: This product has self sealing technology - no sealer is required.

2. For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

### PRODUCT INFO

Product Code 10425

Volume 2.5 US gallon

Shipping Package 2 x 2.5 gallons

Pallet Quantity 48

### TECHNICAL DATA

Coverage	2500 to 3000 ft <sup>2</sup> /gal 61 to 74 m <sup>2</sup> /liter
Buffability	Excellent
Appearance	Milky white
Fragrance	Mild odor, no fragrance added
Removability	Excellent
<small>ASTM D1792-06</small>	
Non-Volatile Solids	25%
<small>ASTM D2834-95 (2008)</small>	
Slip Resistance	Meets requirements
<small>ULTM410</small>	
Detergent Resistance	Excellent
<small>ASTM D3207-92 (2008)</small>	
Specular Gloss (60°F)	>85
<small>ASTM D1455-87 (2008)</small>	
Shelf Life	1 year
<small>ASTM D1791-93 (2008)</small>	
Drying Time	About 25 minutes
Viscosity	<10 centipoise
<small>@ 68°F (20°C)</small>	
Density	8.5 lb/gal @ 68°F
<small>ASTM D1475-98 (2008)</small>	1.03 kg/L @ 20°C
VOC	0.06%
<small>40 CFR Part 59 Subpart C</small>	
Freeze/Thaw	Passes 3 cycles
<small>ASTM D3209-93 (2008)</small>	



Hummelstown, PA 17036

(877) 843-3070

www.ameritechproducts.net